



# UNIVERSAL BEAMS

CERTIFIED TO BRITISH & EUROPEAN STANDARDS

Designation	Mass per metre Kg/m	Depth of Section 'D' mm	Width of Section 'B' mm	Thickness Web 'Y' mm	Flange 'T' mm
457 x 152	52.3	449.8	152.4	7.6	10.9
	59.8	454.6	152.9	8.1	13.3
	67.2	458.0	153.8	9.0	15.0
	74.2	462.0	154.4	9.6	17.0
	82.1	465.8	155.3	10.5	18.9
457 x 191	67.1	453.4	189.9	8.5	12.7
	74.3	457.0	190.4	9.0	14.5
	82.0	460.0	191.3	9.9	16.0
	89.3	463.4	191.9	10.5	17.7
	98.3	467.2	192.8	11.4	19.6
533 x 210	82.2	528.3	208.8	9.6	13.2
	92.1	533.1	209.3	10.1	15.6
	101.0	536.7	210.1	10.8	17.4
	109.0	539.5	210.8	11.6	18.8
	122.0	544.5	211.9	12.7	21.3
610 x 229	101.2	602.6	227.6	10.5	14.8
	113.0	607.6	228.2	11.1	17.3
	125.1	612.2	229.0	11.9	19.6
	139.9	617.2	230.2	13.1	22.1
	149.1	612.4	304.8	11.8	19.7
610 x 305	179.0	620.2	307.1	14.1	23.6
	238.1	635.8	311.4	18.4	31.1
	125.2	677.9	253.0	11.7	16.2
	140.1	683.5	253.7	12.4	19.0
	152.4	687.5	254.5	13.2	21.0
686 x 254	170.2	692.9	255.8	14.5	23.7
	133.9	750.0	264.4	12.0	15.5
	146.9	754.0	265.2	12.8	17.5
	173.0	762.2	266.7	14.3	21.6
	196.8	769.8	268.0	15.6	25.4
838 x 292	175.9	834.9	291.7	14.0	18.8
	193.8	840.7	292.4	14.7	21.7
	226.5	850.9	293.8	16.1	26.8
	200.9	903.0	303.3	15.1	20.2
	224.2	910.4	304.1	15.9	23.9
914 x 305	253.4	918.4	305.5	17.3	27.9
	289.1	926.6	307.7	19.5	32.0
	343.3	911.8	418.5	19.4	32.0
	388.0	921.0	420.5	21.4	36.6

10

Standard Mill lengths available, also cut to size



TEL: 01228 525364  
FAX: 01228 554801