



UNIVERSAL COLUMNS

CERTIFIED TO BRITISH & EUROPEAN STANDARDS

Designation	Mass per metre Kg/m	Depth of Section 'D' mm	Width of Section 'B' mm	Thickness Web 't' mm	Flange 'T' mm	
152 x 152	23.0	152.4	152.2	5.8	6.8	
	30.0	157.6	152.9	6.5	9.4	
	37.0	161.8	154.4	8.0	11.5	
203 x 203	46.1	203.2	203.6	7.2	11.0	
	52.0	206.2	204.3	7.9	12.5	
	60.0	209.6	205.8	9.4	14.2	
	71.0	215.8	206.4	10.0	17.3	
	86.1	222.2	208.1	12.7	20.5	
254 x 254	73.1	254.1	254.6	8.6	14.2	
	88.9	260.3	256.3	10.3	17.3	
	107.1	266.7	258.8	12.8	20.5	
	132.0	276.3	261.3	15.3	25.3	
	167.1	289.1	265.2	19.2	31.7	
	305 x 305	96.9	307.9	305.3	9.9	15.4
		117.9	314.5	307.4	12.0	18.7
136.9		320.5	309.2	13.8	21.7	
158.1		327.1	311.2	15.8	25.0	
198.1		339.9	314.5	19.1	31.4	
240.0		352.5	318.4	23.0	37.7	
282.9		365.3	322.2	26.8	44.1	
356 x 368	129.0	355.6	368.6	10.4	17.5	
	152.9	362.0	370.5	12.3	20.7	
	177.0	368.2	372.6	14.4	23.8	
	201.9	374.6	374.7	16.5	27.0	
356 x 406	235.1	381.0	394.8	18.4	30.2	
	287.1	393.6	399.0	22.6	36.5	
	339.9	406.4	403.0	26.6	42.9	
	393.0	419.0	407.0	30.6	49.2	
	467.0	436.6	412.2	35.8	58.0	
	551.0	455.6	418.5	42.1	67.5	

8

Standard Mill lengths available, also cut to size

ISO 9001 : 2000
REGISTERED FIRM



TEL: 01228 525364
FAX: 01228 554801