



SAFETY DATA SHEET CORROLESS CCI 400 Aerosol

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CORROLESS CCI 400 Aerosol
Product number 4990001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Corrosion inhibitor.

1.3. Details of the supplier of the safety data sheet

Supplier
CORROLESS Corrosion Control
Kelvin Way
West Bromwich
West Midlands
B70 7JZ United Kingdom
t: +44 (0)121 525 5665
f: +44 (0)121 553 2787
info-corroless@axaltacs.com

1.4. Emergency telephone number

Emergency telephone +44 121 524 2245 (not 24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229 Flam. Liq. 2 - H225
Health hazards STOT SE 3 - H336
Environmental hazards Aquatic Chronic 4 - H413

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H336 May cause drowsiness or dizziness.
H413 May cause long lasting harmful effects to aquatic life.

CORROLESS CCI 400 Aerosol

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTER/ doctor if you feel unwell.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P405 Store locked up.</p> <p>P410+P403 Protect from sunlight. Store in a well-ventilated place.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

Contains	HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics
-----------------	---

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Petroleum gases, liquefied		10-30%
CAS number: 68476-85-7	EC number: 270-704-2	REACH registration number: 01-2119485911-31-XXXX
Classification		
Aerosol 1 - H222, H229		
HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		10-30%
CAS number: —	EC number: 919-857-5	REACH registration number: 01-2119463258-33-XXXX
Classification		
Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304		
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics		1-5%
CAS number: —	EC number: 919-446-0	REACH registration number: 01-2119458049-33-XXXX
Classification		
Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

CORROLESS CCI 400 Aerosol

Dowanol PnB Glycol Ether	1-5%
CAS number: 5131-66-8	EC number: 225-878-4
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Keep affected person warm and at rest. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause drowsiness and dizziness. Headache. Nausea, vomiting.
Ingestion	May cause discomfort if swallowed. Diarrhoea. Nausea, vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
Specific treatments	No specific chemical antidote is known to be required after exposure to this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	The product is flammable. Fire-water run-off in sewers may create fire or explosion hazard. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Control run-off water by containing and keeping it out of sewers and watercourses.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO ₂). Carbon monoxide (CO). Acrid smoke or fumes. Metal oxide(s). Oxides of nitrogen.

CORROLESS CCI 400 Aerosol

5.3. Advice for firefighters

Protective actions during firefighting

In case of fire: Evacuate area. No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

CORROLESS CCI 400 Aerosol

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk into spilled material. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe gas, fume, vapours or spray. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Use protective equipment appropriate for surrounding materials.

For emergency responders Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions For professional users only. Eliminate all sources of ignition. Use only in well-ventilated areas. Wear protective clothing as described in Section 8 of this safety data sheet. Earth container and transfer equipment to eliminate sparks from static electricity. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Use only non-sparking tools. Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Remove contaminated clothing and protective equipment before entering eating areas. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at temperatures between 10°C and 25°C. Store in accordance with national regulations. Store in tightly-closed, original container. Avoid contact with oxidising agents.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Petroleum gases, liquefied

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

CORROLESS CCI 400 Aerosol

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

WEL = Workplace Exposure Limit

HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

DNEL

Industry - Dermal; Long term : 208 mg/kg/day

Industry - Inhalation; Long term : 871 mg/m³

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

DNEL

Industry - Inhalation; Short term : 570 mg/m³

Industry - Inhalation; Long term : 1980 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Use explosion-proof ventilating equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for information on material and design requirements and test methods.

Hygiene measures

Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contaminated clothing and protective equipment before entering eating areas. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator.

CORROLESS CCI 400 Aerosol

Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
--	--

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Brown.
Odour	Characteristic.
Flash point	< 21°C
Vapour density	Heavier than air.
Relative density	0.89 +/- 2% kg/litre
Solubility(ies)	Immiscible with water.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. Avoid the accumulation of vapours in low or confined areas.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Oxidising agents. Strong acids.
---------------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	None at ambient temperatures. Heating may generate the following products: Carbon monoxide (CO). Carbon dioxide (CO ₂). Nitrous gases (NO _x).
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

SECTION 12: Ecological Information

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

CORROLESS CCI 400 Aerosol

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste is classified as hazardous waste. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

Disposal methods

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains.

Waste class

08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned.
For further information, contact your local waste authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

14.5. Environmental hazards

CORROLESS CCI 400 Aerosol

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Health and environmental listings	None of the ingredients are listed.
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ATE = Acute Toxicity Estimate
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
Revision date	05/03/2019
Revision	5
Supersedes date	14/12/2018
SDS number	5160
Hazard statements in full	H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.
Mix Ratio	Single Pack

CORROLESS CCI 400 Aerosol

Shelf life 2 year
EU Dir 2

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.