

TECHNICAL DATA SHEET

QUICK DRYING 1K EPOXY PRIMER FINISH - REF: - 45L10

A quick drying 1K Epoxy with superior adhesion to all substrates except stainless. This product is particularly suitable for application to galvanised steel and aluminium without the need for etch primers or other, pre-treatment. The anticorrosive and weathering properties are exceptional, and this product can be applied over an initial quick drying coating or tinted to the desired colour.

PACKAGE SIZE	5 Litre, 2.5 Litre
SHEEN	Matt, Semi-Gloss, Gloss
FLASH POINT	25°C
DRYING TIME @ 20°C	Surface Dry: 15-30 mins
VOLUME SOLIDS	34% (+/- 2%)
RECOMMENDED W.F.T.	125 microns
RECOMMENDED D.F.T.	75 microns
THEORETICAL SPREADING RATE	10-14 SqM/Ltr @ 75 Micron
THINNERS	Anti Bloom THINNERS
SHELF LIFE	12 mths
V.O.C.	575 g/litre

SURFACE PREPERATION

Ensure surface is free from rust, moisture, oil or other surface contamination.

APPLICATION

Spray for best application.

HEALTH & SAFETY

Refer to M.S.D.S prior to use. 151123

Provide adequate ventilation. Prolonged skin contact inhalation of vapour must be avoided. Eye contamination - Flush with eyewash or warm water for 10 mins. Clean hands after use.

Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and Towneley Paints Ltd can accept no liability for the performance of the product or for any loss or damage arising out of such use.