

SAFETY DATA SHEET METAL WORKING SPRAY R208

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name:

METAL WORKING SPRAY

Article number:

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:	TYGRIS Industrial Unit 31, Kyle Road Industrial Estate Irvine Ayrshire KA12 8LE Tel +44 (0) 1294 311 066 Fax +44 (0) 1294 277 115 Email technical@tygrisindustrial.com
Further information obtainable from:	Technical Department
1.4 Emergency telephone number:	Tel +44 (0) 1294 311 066

R208





SAFETY DATA SHEET METAL WORKING SPRAY R208

2. Hazards identification

2.1. Classification of the substance or mixture		
Physical hazards:	Flam. Aerosol 1 - H222	
Health hazards:	EUH066, Lact H362	
Environment hazards:	Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	
2.2. Label elements		
Hazard statements:	H222: Extremely flammable aerosol. H336: May cause drowsiness or dizziness. H410: Very toxic to aquatic life with long lasting effects.	
Hazard pictograms:	GHS02: Flame GHS09: Environmental	
Signal word:	Danger	
Precautionary statements:	 P102: Keep out of reach of children. P210: Keep away from heat/sparks/open flames/hot surfaces No smoking. P211: Do not spray on an open flame or other ignition source. P251: Pressurized container: Do not pierce or burn, even after use. P261: Avoid breathing vapour/spray. P263: Avoid contact during pregnancy/while nursing. P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well-ventilated area. P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501: Dispose of contents/container in accordance with local regulations. 	
Supplementary precautionary statements:	P201: Obtain special instructions before use. P264: Wash contaminated skin thoroughly after handling. P273: Avoid release to the environment. P308+313: IF exposed or concerned: Get medical advice/attention. P391: Collect spillage.	
Additional information:	EUH066: Repeated exposure may cause skin dryness or cracking. H229: Pressurised container: May burst if heated	
2.3. Other hazards		





3. Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CHLORINATED PARAFFIN C14-C17 (51%)

EC	CAS	Index number	CLP Classification	Percent
287-477-0	85535-85-9	-	EUH066 Lact H362 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	30-60%

BUTANE

203-448-7	106-97-8	-	Flam. Gas 1 - H220	1-5%
ISOBUTANE				
200-857-2	75-28-5	-	Flam. Gas 1 - H220	1-5%

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

4. First aid measures

4.1. Description of first aid measures

General information:	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.	
Skin contact:	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.	
Eye contact:	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.	
Ingestion:	DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.	
Inhalation:	Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.	
4.2. Most important symptoms and effects, both acute and delayed		
General information:	NOTE! Effects may be delayed. Keep affected person under observation.	

4.3. Indication of any immediate medical attention and special treatment needed





5. Firefighting measures

5.1 Extinguishing media

Extinguishing media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Aerosol cans may explode in a fire.

5.3. Advice for fire-fighters

Special fire fighting
procedures:Containers close to fire should be removed or cooled with water. Use water to
keep fire exposed containers cool and disperse vapours.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

7. Handling and storage

7.1 Precautions for safe handling

Handling requirements:Keep away from heat, sparks and open flame. Avoid spilling, skin and eye
contact. Ventilate well, avoid breathing vapours. Use approved respirator if air
contamination is above accepted level.7.2. Conditions for safe storage, including any incompatibilities
Storage conditions:Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.7.3. Specific end use(s)Keep away from heat, sparks and open flame. Avoid spilling, skin and eye
contact. Ventilate well, avoid breathing vapours. Use approved respirator if air
contamination is above accepted level.

Specific end use(s): The identified uses for this product are detailed in Section 1.2.





8. Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

BUTANE

Long-term exposure limit (8-hour TWA)	Short-term exposure limit (15-minute)
WEL 600 ppm, 1450 mg/m ³	WEL 750 ppm, 1810 mg/m ³

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment:



Engineering measures:	Provide adequate general and local exhaust ventilation.
Hygiene measures:	DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Respiratory protection:	No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.
Hand protection:	Use protective gloves.
Eye protection:	Wear approved chemical safety goggles where eye exposure is reasonably probable.
Other Protection:	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol
Colour:	Typical
Odour:	Characteristic
Flammability limits:	Lower: 0.8 % Upper: 9.0 %
9.2. Other information	





10. Stability and reactivity

10.1. Reactivity		
10.2. Chemical stability		
Chemical stability:	Stable under normal temperature conditions.	
10.3. Possibility of hazardous reactions		
10.4. Conditions to avoid		
Conditions to avoid:	Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.	
10.5. Incompatible materials		
Incompatible materials:	See section 10.4	
10.6. Hazardous decomposition products		
Fire creates:	Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).	

11. Toxicological information

11.1. Information on toxicological effects		
Skin contact:	Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.	
Eye contact:	Irritating to eyes. May cause chemical eye burns.	
Inhalation:	May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.	
Ingestion:	May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.	
Route of entry:	Inhalation. Skin and/or eye contact.	

12. Ecological information

12.1. Toxicity

Ecotoxicity:

Dangerous for the environment if discharged into watercourses.

- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects



Unit 31, Kyle Road Industrial Estate Irvine, Ayrshire KA12 8LE. Tel: +44 (0) 1294 311 066 technical@tygrisindustrial.com



13. Disposal considerations

13.1. Waste treatment methods

General information:

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14. Transport information

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code





15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
Statutory Instruments:	The Aerosol Dispensers (Amendment) Regulations 2014 No.1130.	
Guidance Notes:	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.	
EU Legislation:	 The Aerosol Dispensers Directive 1975/324 EEC. Regulation (EC) No.1272/2008: The Classification, Labelling and Packaging of substances and mixtures Regulations. Regulation (EC) No. 1907/2006: The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH). 2001/95/EC The General Product Safety Directive (GPSD). Commission Regulation (EU) 2015/830: Requirements for the compilation of safety data sheets (amending REACH). Authorisations (Title VII Regulation 1907/2006): No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006): No specific restrictions of use are noted for this product. 	

15.2. Safety, health and environmental regulations/legislation specific for the substance or mixture

16. Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking. H220: Extremely flammable gas. H222: Extremely flammable aerosol. H362: May cause harm to breast-fed children. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects.
Legal disclaimer	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

